

Motor Data Sheet



Output kW	0.12
Pole	2
Frame Size	56B
Voltage	230/415 50Hz, 440/460/480 60Hz
Motor Series	TAI
Construction	Aluminium
Type	TEFC
Protection	IP55
Insulation Class	F with Class B rise
Ambient	-20°C to +40°C at 1000 MASL
IEC Standard	IEC 60034 & 72
Duty	S1
Full Load RPM	2700
Full Load Current @ 400V	0.36 A
Starting Current Ratio	3.78
Full Load Torque (Nm)	0.43
Starting Torque Ratio	2.49
Break Down Torque Ratio	2.34
Pull Up Torque Ratio	2.13
Efficiency @ 100% load	61.6%
Efficiency @ 75% load	60.6%
Efficiency @ 50% load	54.2%
Power factor @ 100% load	0.79
Power factor @ 75% load	0.68
Power factor @ 50% load	0.54
Noise Level dB (A) @ 1 metre	58
Output kW @ 440/460/480V	0.132/0.138/0.144
Full Load RPM @ 60Hz	3240
Full Load Current @ 440/460/480V	0.33/0.31/0.30 A
Vibration Limit	1.8 mm/sec
Bearing Make	NSK
Bearing Type D.E./N.D.E	Ball/Ball
Bearing Size D.E./N.D.E.	6201ZZ/6201ZZ C3
Motor Mass	3.0 kg
Thermal Protection	Available upon request

Note: This data sheet has been issued for our standard TAI series and is subject to change without prior notice.