

Motor Data Sheet



Output kW	0.09
Pole	8
Frame Size	71A
Voltage	230/415 50Hz, 440/460/480 60Hz
Motor Series	TAI
Construction	Aluminium
Type	TEFC
Protection	IP55
Insulation Class	F with Class B rise
Ambient	-20°C to +40°C at 1000 MASL
IEC Standard	IEC 60034 & 72
Duty	S1
Full Load RPM	665
Full Load Current @ 400V	0.53 A
Starting Current Ratio	2.33
Full Load Torque (Nm)	1.29
Starting Torque Ratio	2.41
Break Down Torque Ratio	2.57
Pull Up Torque Ratio	2.35
Efficiency @ 100% load	43.1%
Efficiency @ 75% load	38.7%
Efficiency @ 50% load	30.7%
Power factor @ 100% load	0.57
Power factor @ 75% load	0.50
Power factor @ 50% load	0.42
Noise Level dB (A) @ 1 metre	52
Output kW @ 440/460/480V	0.099/0.103/0.108
Full Load RPM @ 60Hz	798
Full Load Current @ 440/460/480V	0.48/0.46/0.44 A
Vibration Limit	1.8 mm/sec
Bearing Make	NSK
Bearing Type D.E./N.D.E	Ball/Ball
Bearing Size D.E./N.D.E.	6202ZZ/6202ZZ C3
Motor Mass	5.6 kg
Thermal Protection	Available upon request

Note: This data sheet has been issued for our standard TAI series and is subject to change without prior notice.