

Motor Data Sheet



Output kW	0.12
Pole	8
Frame Size	71B
Voltage	230/415 50Hz, 440/460/480 60Hz
Motor Series	TAI
Construction	Aluminium
Type	TEFC
Protection	IP55
Insulation Class	F with Class B rise
Ambient	-20°C to +40°C at 1000 MASL
IEC Standard	IEC 60034 & 72
Duty	S1
Full Load RPM	650
Full Load Current @ 400V	0.62 A
Starting Current Ratio	2.59
Full Load Torque (Nm)	1.75
Starting Torque Ratio	2.52
Break Down Torque Ratio	2.62
Pull Up Torque Ratio	2.47
Efficiency @ 100% load	47.7%
Efficiency @ 75% load	44.5%
Efficiency @ 50% load	37.0%
Power factor @ 100% load	0.59
Power factor @ 75% load	0.50
Power factor @ 50% load	0.42
Noise Level dB (A) @ 1 metre	52
Output kW @ 440/460/480V	0.132/0.138/0.144
Full Load RPM @ 60Hz	780
Full Load Current @ 440/460/480V	0.56/0.54/0.52 A
Vibration Limit	1.8 mm/sec
Bearing Make	NSK
Bearing Type D.E./N.D.E	Ball/Ball
Bearing Size D.E./N.D.E.	6202ZZ/6202ZZ C3
Motor Mass	6.0 kg
Thermal Protection	Available upon request

Note: This data sheet has been issued for our standard TAI series and is subject to change without prior notice.