

Motor Data Sheet



Output kW	55
Pole	2
Frame Size	250M
Voltage	415/690 50Hz, 440/460/480 60Hz
Motor Series	TCI
Construction	Cast Iron
Type	TEFC
Protection	IP55
Insulation Class	F with Class B rise
Ambient	-20°C to +40°C at 1000 MASL
IEC Standard	IEC 60034 & 72
Duty	S1
Full Load RPM	2970
Full Load Current @ 400V	93.3 A
Starting Current Ratio	8.92
Full Load Torque (Nm)	176.8
Starting Torque Ratio	3.02
Break Down Torque Ratio	2.99
Pull Up Torque Ratio	1.42
Efficiency @ 100% load	94.5%
Efficiency @ 75% load	94.3%
Efficiency @ 50% load	93.2%
Power factor @ 100% load	0.91
Power factor @ 75% load	0.90
Power factor @ 50% load	0.85
Noise Level dB (A) @ 1 metre	88
Output kW @ 440/460/480V	60.5/63.3/66.0
Full Load RPM @ 60Hz	3564
Full Load Current @ 440/460/480V	84.8/81.1/77.8 A
Vibration Limit	3.5 mm/sec
Bearing Make	NSK
Bearing Type D.E./N.D.E	Ball/Ball
Bearing Size D.E./N.D.E.	6314/6314 C3
Motor Mass	
Thermal Protection	PTC 150°C x 3

Note: This data sheet has been issued for our standard TCI series and is subject to change without prior notice.