

Motor Data Sheet



Output kW	75
Pole	4
Frame Size	280S
Voltage	415/690 50Hz, 440/460/480 60Hz
Motor Series	TCI
Construction	Cast Iron
Type	TEFC
Protection	IP55
Insulation Class	F with Class B rise
Ambient	-20°C to +40°C at 1000 MASL
IEC Standard	IEC 60034 & 72
Duty	S1
Full Load RPM	1480
Full Load Current @ 400V	127.7 A
Starting Current Ratio	7.56
Full Load Torque (Nm)	482.5
Starting Torque Ratio	2.54
Break Down Torque Ratio	2.37
Pull Up Torque Ratio	2.11
Efficiency @ 100% load	94.9%
Efficiency @ 75% load	95.2%
Efficiency @ 50% load	94.8%
Power factor @ 100% load	0.90
Power factor @ 75% load	0.89
Power factor @ 50% load	0.84
Noise Level dB (A) @ 1 metre	80
Output kW @ 440/460/480V	82.5/86.3/90.0
Full Load RPM @ 60Hz	1776
Full Load Current @ 440/460/480V	116.1/111.0/106.4 A
Vibration Limit	3.5 mm/sec
Bearing Make	NSK
Bearing Type D.E./N.D.E	Ball/Ball
Bearing Size D.E./N.D.E.	6316/6316 C3
Motor Mass	
Thermal Protection	PTC 150°C x 3

Note: This data sheet has been issued for our standard TCI series and is subject to change without prior notice.