

Motor Data Sheet



Output kW	22
Pole	4
Frame Size	180L
Voltage	415/690 50Hz, 440/460/480 60Hz
Motor Series	TCI
Construction	Cast Iron
Type	TEFC
Protection	IP55
Insulation Class	F with Class B rise
Ambient	-20°C to +40°C at 1000 MASL
IEC Standard	IEC 60034 & 72
Duty	S1
Full Load RPM	1465
Full Load Current @ 400V	38.9 A
Starting Current Ratio	7.67
Full Load Torque (Nm)	143.1
Starting Torque Ratio	2.25
Break Down Torque Ratio	2.69
Pull Up Torque Ratio	1.55
Efficiency @ 100% load	91.9%
Efficiency @ 75% load	92.5%
Efficiency @ 50% load	92.1%
Power factor @ 100% load	0.89
Power factor @ 75% load	0.86
Power factor @ 50% load	0.79
Noise Level dB (A) @ 1 metre	73
Output kW @ 440/460/480V	24.2/25.3/26.4
Full Load RPM @ 60Hz	1758
Full Load Current @ 440/460/480V	35.4/33.8/32.4 A
Vibration Limit	2.8 mm/sec
Bearing Make	NSK
Bearing Type D.E./N.D.E	Ball/Ball
Bearing Size D.E./N.D.E.	6311/6311 C3
Motor Mass	
Thermal Protection	PTC 150°C x 3

Note: This data sheet has been issued for our standard TCI series and is subject to change without prior notice.