

Motor Data Sheet



Output kW	2.2
Pole	2
Frame Size	90L
Voltage	230/415 50Hz, 440/460/480 60Hz
Motor Series	TCI
Construction	Cast Iron
Type	TEFC
Protection	IP55
Insulation Class	F with Class B rise
Ambient	-20°C to +40°C at 1000 MASL
IEC Standard	IEC 60034 & 72
Duty	S1
Full Load RPM	2890
Full Load Current @ 400V	4.61 A
Starting Current Ratio	8.11
Full Load Torque (Nm)	7.2
Starting Torque Ratio	3.00
Break Down Torque Ratio	3.18
Pull Up Torque Ratio	2.22
Efficiency @ 100% load	84.0%
Efficiency @ 75% load	84.4%
Efficiency @ 50% load	82.5%
Power factor @ 100% load	0.83
Power factor @ 75% load	0.75
Power factor @ 50% load	0.61
Noise Level dB (A) @ 1 metre	68
Output kW @ 440/460/480V	2.42/2.53/2.64
Full Load RPM @ 60Hz	3468
Full Load Current @ 440/460/480V	4.19/4.00/3.84 A
Vibration Limit	1.8 mm/sec
Bearing Make	NSK
Bearing Type D.E./N.D.E	Ball/Ball
Bearing Size D.E./N.D.E.	6205ZZ/6205ZZ C3
Motor Mass	22 kg
Thermal Protection	Available upon request

Note: This data sheet has been issued for our standard TCI series and is subject to change without prior notice.